# FORGED STEEL (A 105) HORIZONTAL LIFT CHECK VALVE CLASS-800 (REDUCED BORE)

## **Specification & Features:**

Conforming To BS: 5352 / API 602 BSEN - 15761

Screwed female ends to BSP / NPT Socket Welded Ends To ANSI B 16.11

Bolted cover, Sturdy in design & superb in quality.

## **Pressure / Temperature ratings**

Temperature °Celsius	-29° +38°	93.5 <sup>°</sup>	149 <sup>°</sup>	204°	260°	316 <sup>°</sup>	343 <sup>°</sup>	371 <sup>°</sup>	399 <sup>°</sup>	427 <sup>°</sup>	<b>*</b> 454	<b>★</b> 482 <sup>°</sup>	<b>*</b> 510	<b>*</b> 538°
Pressure bar	136	124	121	117	110	101	99	98	93	76	49	32	19	10





## **Materials of Construction**


NAME OF PART	MATERIAL	STANDARD
Body & Cover	Forged Steel	ASTM A 105
Body Ring & Disc	Stainless Steel	ASTMA 182 F 6A
Gasket	Spiral Wound S.S. 304 Graphite Filled	
Fastners	Alloy Steel	ASTM 193 B7 / A194 2H

Test Pressure: Body: 207 Bar (Hyd.)

Seat: 152 Bar (Hyd.)

#### Sizes / Dimensions

Size	es	Dimensions				
Inches	mm	Α	В	С		
1/2	15	80	1/2	58		
3/4	20	88	3/4	62		
1	25	100	1	75		
1-1/2 40		145	1-1/2	98		
2 50		170	2	120		











<sup>\*</sup> Permissible but not recommended for prolonged usage above 427 celsius